

1000


falco



FALCO 100CC.

Telaio omologato CIK/FIA 81/CH/08, tubo scocca CR-MO 32/30 mm, assale Ø 40 mm o Ø 50 mm, impianto frenante **RUNNER** (CIK/FIA 84/FR/08), tubo freno rivestito in acciaio col. oro, pinza freno 4 pistoncini con regolazione rapida gioco pastiglie, supporto marmitta regolabile in altezza e rotazione, stabilizzatore anteriore con 2 morsetti anodizzati.

CIK/FIA homologated chassis 81/CH/08, main frame tube CR-MO Ø 32/30 mm, rear axle Ø 40 mm or 50mm Ø, **RUNNER** braking system (CIK/FIA 84/FR/08), with braided steel gold brake lines, rear calliper with 4 pistons with quick pad clearance adjustment, exhaust holder bracket with adjustable height and rotation, front stabilizer with 2 anodised clamps.



125


falco



FALCO 125

Telaio omologato CIK/FIA 81/CH/08, tubo scocca CR-MO 32/30 mm - Assale Ø 40 mm o Ø 50 mm, impianto frenante **RUNNER** (CIK/FIA 83/FR/08), tubo freno rivestito in acciaio col. oro, pinza freno anteriore con centraggio disco regolabile, pinza freno posteriore 4 pistoncini con regolazione rapida gioco pastiglie, stabilizzatore anteriore con 2 morsetti anodizzati.

CIK/FIA homologated chassis 81/CH/08 - Main frame tube CR-MO Ø 32/30 mm, rear axle Ø 40 mm or 50 mm, **RUNNER** braking system (CIK/FIA 83/FR/08) with braided steel gold brake lines, rear calliper with 4 pistons with quick pad clearance adjustment, innovative front calliper system with adjustable disk centering, front stabilizer with 2 gold anodised clamps.



4-CYCLE

falco



FALCO 4 tempi

Telaio omologato CIK/FIA sviluppato per motori 4-tempi. Nuovo impianto frenante omologato **RUNNER**, doppia pompa freno, tubo freno rivestito, supporto sedile staccabile con morsetto anodizzato, assale da 40mmØ o 50mm Ø. Su richiesta, può essere fornito con impianto frenante anteriore omologato.

CIK/FIA homologated chassis designed for 4-cycle engines. It is supplied with homologated **RUNNER** braking system, double brake pump, covered brake tube, removable seat support with clamp, 40mm Ø or 50mm Ø rear axle.

On request, it can be supplied with homologated front brake system.

